



The 705 is a compact 2-way system suitable for stand or bookshelf mounting. The FS-700 speaker stand is recommended and can be screwed directly into the base of the speaker. Along with the 703, 704 and HTM7, the sloping top and front baffle are formed from a single piece of ply. This makes the cabinet stronger than if two separate panels had been used and the curved profile of the lip in of the tweeter benefits the driver's response by reducing diffraction from any sharp edge.

<i>Description:</i>	2-way vented-box system	<i>Impedance:</i>	8Ω (minimum 4.6Ω)
<i>Frequency range (-6dB):</i>	43Hz and 50kHz	<i>Dimensions:</i>	H 420mm W 222mm D 319mm H 16.6" W 8.7" D 12.6"
<i>Power handling:</i>	120W into 8Ω	<i>Weight:</i>	9.5 kg / 21 lbs.
<i>Sensitivity:</i>	89dB spl (2.83V, 1m)		

## B&W Bowers & Wilkins

B&W Group Ltd  
Dale Road  
Worthing West Sussex  
BN11 2BH England

T +44 (0) 1903 221800  
F +44 (0) 1903 221801  
info@bwgroup.com  
www.bwspeakers.com

UK Group (UK Sales)  
T +44 1903 221 500  
E uksales@bwgroup.com

B&W Group North America  
T +1 978 664 2870  
E marketing@bwgroupusa.com

B&W Group Asia Ltd  
T +852 2 869 9916  
E showroom@bwgroup.hk