

ASW 10CM



This versatile subwoofer compliments the rest of the CM range with the powerful, deep bass that has come to be expected from B&W's range of subwoofers.

Wrapped in an exquisitely veneered cabinet, the 10 inch dual voice coil paper/Kevlar® driver is driven and controlled by the mega efficient 500W audiophile standard Class D amplifier and switch mode power supply, delivering immense power when the signal demands.

This combination can move vast amounts of air yet not lose any of the control that is necessary for accurate low-frequency output.

Description	Active closed-box subwoofer system
Drive unit	ø250mm (10 in) paper/Kevlar® cone long-throw 76mm (3 in) dia voice coil - dual suspension diecast chassis
Frequency range	-6dB at 18Hz and 25/140Hz adjustable (EQ at A)
Frequency response	±3dB 25Hz – 40/140Hz adjustable (EQ at A)
Base Extension	-6dB at 18Hz (position A) -6dB at 23Hz (position B) -6dB at 28Hz (position C)
Low-pass filter	Active 4th-order, variable cut-off frequency

Amplifier	Power output: 500W Rated power consumption: 94W Standby power consumption: 0.8W Input impedance: 33kV Signal / noise: >80dB Functions: Input level (line in) Input level (speaker in) Low-pass filter frequency Low-pass filter bypass Bass extension Bass roll-off alignment Auto sense on/standby Phase switch Inputs: Line In (RCA Phono) Speaker in (Binding post) 12V trigger (3.5mm jack)
Dimensions	Height: 325mm (12.8 in) (not including feet) Width: 325mm (12.8 in) Depth: 362mm (14.3 in) (including grille and controls)
Net weight	15.5kg (34.4 lb)
Finishes	Gloss Black

B&W Bowers & Wilkins

B&W Group Ltd
Dale Road
Worthing West Sussex
BN11 2BH England
T +44 (0) 1903 221800
F +44 (0) 1903 221801
info@bwgroup.com
www.bwspeakers.com

UK Group (UK Sales)
T +44 1903 221 500
E uksales@bwgroup.com

B&W Group North America
T +1 978 664 2870
E marketing@bwgroupusa.com

B&W Group Asia Ltd
T +852 2 869 9916
E showroom@bwgroup.hk