


ASW™2000

Active Subwoofer

Product Summary

- B&W has achieved such high audio quality in the ASW 2000 by utilizing the very best components, together with the technical innovations for which we are renowned. These include B&W's unique Flowport™ system, a new ultra-low frequency 12-inch drive unit which utilises a stiffer, lighter die cast chassis to minimize unwanted resonance.
- To ensure fewer demands are imposed on your main amplifier, the ASW 2000 features an audiophile-grade 175W amplifier. This supplies greater power in reserve to meet the demands of home theatre sound tracks.

Technical highlights



Flowport™: Golf ball aerodynamics theory points the way towards lower distortion reflex ports. Dimples improve the way the air flows over the surface of any object. In the case of reflex ports, they offer a significant improvement over simply flaring the port ends in reducing air flow turbulence at each end of the port; so you get less chuffing noise and less compression at high sound levels.



European Home Theatre
Loudspeaker 1998-1999
Eisa Awards



Description	Active vented-box subwoofer system with magnetic shielding	Net Weight	35kg (75lb)
Drive Unit	1 x 300mm (12in) dia long-throw	Dimensions	Height: 500mm Width: 550mm Depth: 500mm
Frequency response	± 3dB 22Hz – 40/140Hz adjustable	Finishes	Cabinet: Black Ash vinyl Grille: Black cloth
Input impedance	22k		
Amplifier	175W continuous		
Internal Volume	70 litres		



LISTEN AND YOU'LL SEE