

ASW850

Active Subwoofer

Product Summary

- Sharing the same 1000W amplifier as the smaller ASW 800, the ASW 850 provides over 50% more output with its larger cabinet and 380mm (15 in) driver, making it the ideal solution for the largest high-end installations.
- Built to the same exacting standards and with similar ingredients as the smaller ASW 800, the larger Matrix-braced cabinet and 380mm (15 in) diameter driver of this prodigious performer together provide not only the greater output levels needed for the largest listening rooms, but also plumb greater depths in terms of bass extension.
- So, no matter whether you want to experience the thrill of an action film or recreate the event of a live performance in a large concert hall, the ASW 850 provides the necessary bass extension and power to enable you to do it.



Description	Active closed-box subwoofer system	Inputs:	Line In (RCA Phono)
Drive units	φ380mm (15 in) paper/Kevlar® cone long-throw	Outputs:	Line Out (RCA Phono) high-passed Link Out (RCA Phono)
Frequency response	±3dB 18Hz - 31/110Hz adjustable (EQ at A)	Low-pass filter	Active 2nd -order, variable cut-off frequency
Amplifier	Power output: 1000W continuous Rated power consumption: 150W Input impedance: 33kΩ Signal / noise: >90dB Functions: Input level Low-pass filter frequency Low-pass filter bypass Bass roll-off alignment Auto sense on/standby Phase switch	High-pass filter	Active 3rd -order -6dB at 80Hz
		Dimensions	Height: 529mm (not including feet) Width: 562mm Depth: 522mm (including grille and controls)
		Finishes	Cabinet: Black Ash, Cherrywood and Red Stained Cherrywood Real wood veneers Grille: Black cloth