

CM9

B&W

Bowers & Wilkins



If it's hard to put the sound of the CM9 into words, that's just as well. This top-of-the-range floorstanding speaker will fill even the largest domestic spaces with music so richly detailed, and so startlingly lifelike, that it will leave you speechless.

The three-way CM9 delivers truly commanding bass with the aid of twin 165mm paper/Kevlar® cone drive units. An FST® driver, with its characteristic compression surround supporting the outer edge of the distinctive Kevlar® cone, is specially developed for outstanding midrange performance. The CM9's Nautilus™ tube-loaded aluminium dome tweeter keeps high frequencies crisp and sharp all the way up to 50kHz and beyond.

The quality of CM Series drive units has made it possible to use minimalist crossovers throughout the whole range. The resulting gentle transition between drivers avoids the unnaturally rapid changes in dispersion that bedevil more complex designs, while the high quality components, carefully chosen after exhaustive listening tests, ensure that as little as possible gets between you and the sound of the original recording.

All CM Series speakers come with aluminium driver trims. Grilles attach magnetically, so there are no unsightly grille-mounting features to spoil the clean lines of the speaker's façade. For the finish, you can choose either one of two real-wood veneers in Rosenut or Wengé, or a highly polished gloss black.

Description	3-way vented-box system	Drive Units	1x ø25mm (1 in) aluminium dome high-frequency 1x ø150mm (6 in) woven Kevlar® cone FST midrange 2x ø165mm (6.5 in) paper/Kevlar® cone bass
Frequency Range	-6dB at 30Hz and 50kHz	Dimensions	Height: 1025mm (40.4 in) (including plinth, not feet) Width: 200mm (7.9 in) (cabinet only) Depth: 300mm (11.8 in) (cabinet only) 321mm (12.6 in) (including grille / terminals; not plinth) 370mm (14.6 in) (including plinth)
Frequency Response	56Hz - 22kHz ±3dB on reference axis	Finishes	Wenge, Rosenut, Gloss Black
Sensitivity	89dB spl (2.83V, 1m)		
Nominal Impedance	8V (minimum 3.0V)		
Recommended Amp. Power	30W - 200W into 8Ω on unclipped programme		

B&W Bowers & Wilkins

B&W Group Ltd
Dale Road
Worthing West Sussex
BN11 2BH England
T +44 (0) 1903 221800
F +44 (0) 1903 221801
info@bwgroup.com
www.bwspeakers.com

UK Group (UK Sales)
T +44 1903 221 500
E uksales@bwgroup.com

B&W Group North America
T +1 978 664 2870
E marketing@bwgroupusa.com

B&W Group Asia Ltd
T +852 2 869 9916
E showroom@bwgroup.hk