

FPM 4

B&W

Bowers & Wilkins



The FPM4 uses the same 4" Kevlar® cone bass/midrange drivers and Nautilus™ tube-loaded tweeter as the FPM5, but in a shorter enclosure that matches the height of 42-inch plasma screens, yet concedes little in bass extension. Like the FPM5 it's a 2 1/2-way configuration that allows wider dispersion of sound in the midrange – essential when used horizontally as a centre speaker. With complete timbre matching between the systems in the range, feel free to use a longer model at centre to harmonise with the longer dimension of the screen.

Bass is augmented by Flowport, and is remarkable for such a small enclosure. Kevlar® ensures the midrange is clear and detailed, right where the ear is at its most discerning, and the tweeter extends way beyond the limits of human hearing to make the most of SACD and DVD-A recordings.

Description: 2.5-way vented-box system
Frequency Range: -6dB at 65Hz and 42kHz
Frequency Response: 72Hz – 22kHz ±3dB on reference axis
Sensitivity: 88dB spl (2.83V, 1m)
Power Handling: 25W - 120W into 8ohms on unclipped programme

Normal Impedance: 8 ohms (minimum 4 ohms)
Dispersion: Description: w/in 2dB of reference response
Horizontal: over 40° arc
Vertical: over 10° arc
Dimensions: H 563mm W 170mm D 102mm
H 22.2" W 6.7" D 4"
(including wall plate)
Weight: 4.8 kg / 10.5 lbs.

B&W Bowers & Wilkins

B&W Group Ltd
Dale Road
Worthing West Sussex
BN11 2BH England

T +44 (0) 1903 221800
F +44 (0) 1903 221801
info@bwgroup.com
www.bwspeakers.com

UK Group (UK Sales)
T +44 1903 221 500
E uksales@bwgroup.com

B&W Group North America
T +1 978 664 2870
E marketing@bwgroupusa.com

B&W Group Asia Ltd
T +852 2 869 9916
E showroom@bwgroup.hk