

# FPM 5



With a height to match 50-inch plasma screens, the FPM5 is a 2 1/2-way system featuring a pair of 4" diameter Kevlar® cone bass/midrange drivers, either side of a Nautilus™ tube-loaded tweeter. The 2 1/2-way configuration, where one of the drivers is rolled off above 180Hz, ensures better horizontal dispersion when the speaker is placed in horizontal orientation – typically for centre channel use – enabling you to hear that all-important dialogue wherever you sit.

If sinking your plasma screen into the wall, do the same with any of the FPM models to leave just the frame protruding. It's simply a choice between discreet and ultra discreet.

**Description:** 2.5-way vented-box system  
**Frequency Range:** -6dB at 62Hz and 42kHz  
**Frequency Response:** 69Hz – 22kHz ±3dB on reference axis  
**Sensitivity:** 88dB spl (2.83V, 1m)  
**Power Handling:** 25W - 120W into 8 ohms on unclipped programme

**Normal Impedance:** 8 ohms (minimum 4 ohms)

**Dispersion:** Description: w/in 2dB of reference response  
Horizontal: over 40° arc  
Vertical: over 10° arc

**Dimensions:** H 665mm W 170mm D 102mm  
H 26.2" W 6.7" D 4"  
(including wall plate)

**Weight:** 5.5 kg / 12 lbs.

## B&W Bowers & Wilkins

B&W Group Ltd  
Dale Road  
Worthing West Sussex  
BN11 2BH England

T +44 (0) 1903 221800  
F +44 (0) 1903 221801  
info@bwgroup.com  
www.bwspeakers.com

UK Group (UK Sales)  
T +44 1903 221 500  
E uksales@bwgroup.com

B&W Group North America  
T +1 978 664 2870  
E marketing@bwgroupusa.com

B&W Group Asia Ltd  
T +852 2 869 9916  
E showroom@bwgroup.hk