



# HTM61

The larger of two centre channels in the new 600 Series, the HTM61 is ideal for delivering important dialogue in a room-filling, high-performance home theatre system.

This is the second model in the new 600 Series to see a significant change to the driver complement. The outgoing HTM61 is a 3-way system, but only had a single bass driver. Here, we follow the line-up of the CM Centre 2, with two 6.5-in bass drivers and a smaller FST™ midrange. The Decoupled Double Dome Tweeter has also been moved upwards, to better align with the tweeters of the 683, which would make a great partner for this speaker in home theatre system. Like the HTM62, the ports are at the rear. This concept was retained for the centre speakers because of the more restrictive requirements on frontal area.



Technical features	Decoupled Double Dome aluminium tweeter with Nautilus™ tube loading Kevlar® brand fibre cone FST™ midrange driver Dual-layer aluminium cone bass driver Flowport™	
Description	3-way vented-box system	
Drive units	1x ø25mm (1 in) aluminium dome high-frequency 1x ø100mm (4 in) woven Kevlar® cone FST™ midrange 2x ø165mm (6.5 in) aluminium cone bass	
Frequency range	-6dB at 42Hz and 50 kHz	
Frequency response	50Hz - 22 kHz ±3dB on reference axis	
Dispersion	Within 2dB of reference response Horizontal: over 20° arc Vertical: over 60° arc	
Sensitivity	88dB spl (2.83V, 1m)	
Harmonic distortion	2nd and 3rd harmonics (90dB, 1m) <1% 95Hz - 22 kHz <0.5% 180Hz - 20 kHz	
Nominal impedance	8Ω (minimum 3.0Ω)	
Crossover frequency	400Hz, 4kHz	
Recommended amplifier power	30W - 150W into 8Ω on unclipped programme	
Max. recommended cable impedance	0.1Ω	
Dimensions	Height:	218mm (8.6 in)
	Width:	590mm (23.2 in)
	Depth:	304mm (12 in) cabinet, grille and terminals
Net Weight	17.2kg (37.8 lb)	
Finishes	Cabinet:	Grille:
	Black Ash	Black