



HTM62

The smaller of the two centre speakers in the new 600 Series is the perfect solution for a modestly sized, but high performance, home theatre system.

It features the new Decoupled Double Dome tweeter and twin 5-inch Kevlar® bass/midrange drive units, making it a great acoustic match to both the 686 and the 684. It's a two-way system, and sees a slight increase in width over the outgoing HTM62, but the height has been reduced slightly to allow for easier positioning. Another difference is the upward relocation of the tweeter, to bring it in line with the position of the 684, for improved integration across the front of a home theatre set up. A rear-firing port is retained.



Technical features	Decoupled Double Dome aluminium tweeter with Nautilus™ tube loading Kevlar® brand fibre cone bass/midrange Flowport™
Description	2-way vented-box system
Drive units	1x ø25mm (1 in) aluminium dome high-frequency 2x ø130mm (5 in) woven Kevlar® cone bass/midrange
Frequency range	-6dB at 48Hz and 50kHz
Frequency response	70Hz - 22kHz ±3dB on reference axis
Dispersion	Within 2dB of reference response Horizontal: over 20° arc Vertical: over 60° arc
Sensitivity	87dB spl (2.83V, 1m)
Harmonic distortion	2nd and 3rd harmonics (90dB, 1m) <1% 120Hz - 22kHz <0.5% 180Hz - 20kHz
Nominal impedance	8Ω (minimum 4.0Ω)
Crossover frequency	4kHz
Recommended amplifier power	25W - 120W into 8Ω on unclipped programme
Max. recommended cable impedance	0.1Ω
Dimensions	Height: 160mm (6.3 in) Width: 480mm (18.9 in) Depth: 279mm (11 in) cabinet, grille and terminals
Net Weight	7.9kg (17.3 lb)
Finishes	Cabinet: Black Ash Grille: Black