

LCR3

B&W
Bowers & Wilkins



The LCR3 has the same technological make-up as the DM303. The product is magnetically shielded and its symmetrical design means it can be used in either horizontal or vertical orientation, which makes it ideal for centre channel or other applications where the speaker needs to be placed close to a TV. The front baffle is moulded in inert mica filled polypropylene, which has a subtly curved outline and is dimpled to echo the theme of Flowport at the back; itself elegantly combined with easy-access terminal panel that can accept all common terminations.

Description:

2-way vented-box
centre system

Impedance:

8Ω (minimum 3.3Ω)

Frequency range (-6dB):

60Hz and 30kHz

Dimensions:

H 152mm W 418mm D 221mm
H 6" W 16.5" D 8.7"

Power handling:

100W into 8Ω

Weight:

5 kg / 11 lbs.

Sensitivity:

90dB spl (2.83V, 1m)

B&W Bowers & Wilkins

B&W Group Ltd
Dale Road
Worthing West Sussex
BN11 2BH England
T +44 (0) 1903 221800
F +44 (0) 1903 221801
info@bwgroup.com
www.bwspeakers.com

UK Group (UK Sales)
T +44 1903 221 500
E uksales@bwgroup.com

B&W Group North America
T +1 978 664 2870
E marketing@bwgroupusa.com

B&W Group Asia Ltd
T +852 2 869 9916
E showroom@bwgroup.hk