Floor-standing loudspeaker system

Product Summary

- The essential difference between the P6 and the other speakers in this series is a B&W trademark the free-mounted tweeter "tweeter on top".
- Combining a 165mm dia Cobex® bass drive unit with the Kevlar® bass/mid-range drive unit and a larger cabinet volume, the P6 delivers high power handling and efficiency with superb bass extension.

Technical highlights



Kevlar®: B&W developed and patented the method of using Kevlar® for loudspeaker cones to reduce unwanted standing waves. DuPont originally created Kevlar® for use in bulletproof vests.

 Tweeter on top: B&W's Tweeter on top technology ensures that the sound remains focused and time-sensitive and that the stereo-image is presented with unparalleled three dimensional accuracy.



Description 3-way 4th order vented box system Power Handling 30W - 150W into 8 ohms on **Drive Units** 1 x 25mm metal dome - high unclipped programme 1 x 165mm Kevlar® - bass/midrange Height: 1000mm Width: 200mm Dimensions 1 x 165mm Cobex* - bass Depth: 316mm Frequency Response 40Hz – 20Hz ±2dB on reference axis Black Ash, Rosenut, Cherrywood Finish Sensitivity 90dB spl(2.83V 1m) Grille: Black Cloth Nominal Impedance 8 ohms (minimum 3.5 ohms)

