

CLASSE

CA-2200 POWER AMPLIFIER



The CA-2200 is simply our best stereo amplifier. It is rated at 200w per channel at 8 ohms. Design features include balanced circuitry, overbuilt power supplies and oversized output stages to ensure the highest performance at every output level, with any loudspeaker.

Specifications

Model (balanced inputs)	CA-2200	Noise	FFT noise floor peaks all below -95dBV (with terminated inputs)
Voltage gain	29.1dB	S/N ratio (relative to 1kHz sine wave full level output into 8Ω)	108dB
Bandwidth	155kHz (-3dB) 22kHz (-0.1dB)	Height	8.75" (222 mm)
Phase	< -10° (22kHz)	Depth (excluding connectors)	18.5" (470 mm)
Sensitivity	1.4Vrms	Width	17.5" (445 mm)
Power/channel (continuous) (120VAC line, 1kHz signal regulated to 1% THD + noise into resistive load, all channels driven)		Gross weight	92 lbs (42 kg)
Load (resistive)		Net weight	80 lbs (36 kg)
8Ω	200W	Idle power consumption	166W
4Ω	400W	Rated power consumption	480W
THD + noise (unweighted, 10Hz - 500kHz bandwidth, 1Vrms/1kHz input)			
Load (resistive)			
none	0.002%		
8Ω	0.003%		
4Ω	0.005%		