



The CDP-300 offers six high-quality analog audio channels as well as progressively scanned and scaled analog and digital video.

The CDP-300 can output video for all rates covered in the HDTV specification, including 1080p on HDMI. As with other Delta series disc players, the CDP-300 features a TFT preview screen and touch-screen control to enhance and simplify operation.

Specifications

Model	CDP-300	Audio outputs	6 x RCA 2 x XLR Coax S/PDIF 1 x RCA AES/EBU 1 x XLR Optical 1 x Toslink
Frequency response	8Hz – 20kHz balanced +0dB/-0.1dB	Video outputs	HDMI Component (progressive scan) S Video Composite
(THD + noise)	8Hz – 20kHz single ended +0dB/-0.7dB	Formats supported	CD, CD-R, CD-RW, DVD Audio & Video, VCD, SVCD, MP3, WMA, DVD-R, DVD+R, DVD-RW, DVD+RW
Signal to noise ratio	0.001% ref 1kHz 0.001% ref 10Hz – 20kHz	Internal scaling	480i (via all video outputs) 480p (via component & HDMI) 720p/ 1080i/ 1080p (via HDMI)
Channel separation	107dBFS (unweighted), 22Hz- 22kHz based on a 1kHz, 0dBFS, CD resolution reference signal	Weights & measurements	
D/A converter	3 x Cirrus Logic CS4398	Width	17.5" (455 mm)
Audio sample rate	192 kHz	Depth	16.5" (419 mm) (excluding connectors)
Output level balanced	4 Vrms	Height	4.75" (121 mm)
Output level single ended	2 Vrms	Gross weight	35 lbs (16 kg)
Power consumption	72W	Net weight	26 lbs (12 kg)