



Description

The RB-1552 has all of the advanced design features of the higher powered RB-1582, but with a slightly more modest output of 2 x 130 watts into 8 ohms. The rock solid power supply, select grade components, and refined sound are all hallmarks of Rotel's nearly 50 years in audio design and manufacturing. RB-1552 features include 12-volt triggers for remote operation and an IEC detachable power cord.

Specifications

Power Configurations	2 x 130 watts (20Hz-20kHz, <0.03%, 8 Ohms)	Frequency Response (+/-1dB)	4 - 100kHz (+0.5dB, -3dB)
Watts/Channel	130 watts, all channels driven, 8 ohm load, 20-20kHz	S/N Ratio (IHF A)	120dB
THD (20-20,000Hz) 8 Ohms, all channels driven	< 0.03%	Power Consumption	400 watts
IM Distortion	< 0.03%	Dimensions (W x H x D) mm	431 x 144 x 340 mm
Damping Factor (8 Ohms)	500	Dimensions (W x H x D) in	17 x 5.25 x 13.4 in
Input Sensitivity / Impedance	1.5V / 12kOhms	Front Panel Height	3 U (5.25")
		Shipping Weight	31.6 lbs.

www.rotel.com

The Rotel Co. Ltd.
10-10 Shinsen-Cho
Shibuya-Ku,
Tokyo 150, Japan

Rotel of America
54 Concord St.
N. Reading, MA 01864
USA
T +1 978 664 3820
F +1 978 664 4109

Rotel Europe
Dale Road
Worthing
West Sussex BN11 2BH, UK
T +44 (0) 1903 221 763
F +44 (0) 1903 221 525