



CM Centre S2

CM Centre S2 features an improved Decoupled Double Dome tweeter, ideal for delivering the clarity needed for dialogue. CM Centre S2 also features two 5-inch drivers that use Kevlar cones, for an ideal mix of punch and precision. The result, combined with the Decoupled Double Dome tweeter, is a centre speaker that is the perfect partner for CM8 S2 in a Home Theatre set up.



Technical features	Nautilus tube loaded Decoupled Double Dome aluminium tweeter Kevlar® brand fibre cone bass / midrange Flowport™ Magnetic shielding
Description	2-way vented-box system
Drive units	1x ø25mm (1 in) Decoupled Double Dome aluminium high-frequency 2x ø130mm (5 in) woven Kevlar cone bass/midrange
Frequency range	-6dB at 48Hz and 50kHz
Frequency response	70Hz - 28kHz ±3dB
Dispersion	Within 2dB of reference response Horizontal: over 60° arc Vertical: over 20° arc
Sensitivity	87dB spl (2.83V, 1m)
Harmonic distortion	2nd and 3rd harmonics (90dB, 1m) <1% 100Hz - 22kHz <0.5% 200Hz - 22kHz
Nominal impedance	8Ω (minimum 4.3Ω)
Crossover frequency	4kHz
Recommended amplifier power	30W - 120W into 8Ω on unclipped programme
Max. recommended cable impedance	0.1Ω
Dimensions	Height: 166.5mm (6.6 in) Width: 480mm (18.9 in) Depth: 260mm (10.2 in) cabinet only 275mm (10.8 in) including grille and terminals
Net weight	11.5kg (25.3 lb)
Finishes	Cabinet: Grille: Rosnut Black Gloss Black Black Satin White Grey