



# Listening is believing

Employing a pair of 6 inch glass fibre bass/midrange cone and a soft dome high sensitivity tweeter, the new CWM Cinema 6 is a cost-effective alternative to B&W's CWM Cinema centre-channel speaker. The speaker combines brilliant sound quality with compactness and versatility: it's small enough to be mounted within existing stud walls, and can be used as a left, right and surround-sound speaker if required.

## Technical Specifications

### Technical features

### Nautilus™ tube-loaded tweeter Woven glassfibre bass/midrange driver

Description	2-way in-wall speaker system
Drive units	1x ø25mm (1 in) tube-loaded softdome high-frequency 2 x ø2x 160mm (6 in) woven glassfibre cone bass/midrange
Frequency range	-6dB at 50Hz and 30kHz
Frequency response	60Hz – 22kHz ±3dB on reference axis
Sensitivity	92dB spl (2.83V, 1m)
Nominal impedance	8Ω (minimum 5.0Ω)
Crossover frequency	3.5kHz
Recommended amplifier power	150W continuous into 8Ω on unclipped programme
Frame size	Height: 255mm (10.1 in) Width: 369mm (14.6 in)
Cut-out size	Height: 223mm (8.8 in) Width: 338mm (13.3 in)
Min depth req.	90mm (3.6 in) behind ceiling surface 8mm (0.3 in) in front of ceiling surface
Net Weight	2.9kg (6.4 lb)
Finishes	Semi-matt white suitable for customising or pre-painting
Accessories	Pre-mount kit for new construction: PMK W8 Backbox: BB W8



## B&W Bowers & Wilkins

B&W Group Ltd  
Dale Road  
Worthing West Sussex  
BN11 2BH England

T +44 (0) 1903 221800  
F +44 (0) 1903 221801  
info@bwgroup.com  
www.bowers-wilkins.com

B&W Group (UK Sales)  
T +44 (0) 1903 221 500  
E uksales@bwgroup.com

B&W Group North America  
T +1 978 664 2870  
E marketing@bwgroupusa.com

B&W Group Asia  
T +852 2 790 8903  
E info@bwgroup.hk

Nautilus and Flowport are trademarks of B&W Group Ltd.  
Copyright © B&W Group Ltd. E&OE.  
Design Thomas Manss & Company. Printed in the U.S.A.  
B&W Group Ltd reserves the right to amend details of the specification without notice in line with technical developments.