



## See nothing, hear everything

The CWM7.5 contains a 130mm(5in) bass/mid-range Aramid Fibre driver set in a die-cast chassis and a Nautilus™ tube loaded 25mm (1in) soft dome tweeter. Utilising proven technologies such as Flowport™ the speaker also features the best quality components such as having Mundorf components on the crossover. It has a critically formed baffle constructed from glass reinforced ABS and the extra-rigidity provides a much cleaner sound reproduction.

## Technical Specifications

<b>Description</b>	2-way in-wall system
<b>Drive units</b>	1x ø25mm (1in) Nautilus™ tube loaded soft dome tweeter 1x ø130mm (5in) blue Aramid Fibre cone bass/midrange
<b>Frequency Range (-6dB)</b>	49Hz – 28kHz
<b>Recommended Amp Power</b>	25 – 150w
<b>Sensitivity SPL (2.83V, 1m)</b>	86dB
<b>Impedance Nominal (min)</b>	6Ω (5.2Ω)
<b>Frame height</b>	356mm (14in)
<b>Frame width</b>	212mm (8.5in)
<b>Cut-out height</b>	331mm (13in)
<b>Cut-out width</b>	187mm (7.4in)
<b>Cut-out height w/PMK</b>	336mm (13.2in)
<b>Cut-out width w/PMK</b>	192mm (7.6in)
<b>Depth behind surface</b>	102mm (4.02in)
<b>Reservoir box height</b>	385mm (15.2in)
<b>Reservoir box width</b>	181mm (7.1in)
<b>Reservoir box depth</b>	60mm (2.4in)
<b>Protrusion</b>	8mm (0.32in)
<b>PMK</b>	7.5W