

# FPM 6

**B&W**  
Bowers & Wilkins



With an enclosure height to match the height of 60-inch plasma screens, the FPM6 is the largest model in the FPM Series. Compared to the other models, its enclosure is not only longer, it's wider too, which allows the use of two 5" Kevlar® cone bass/midrange drivers each side of the Nautilus™ tube-loaded tweeter. Higher output level capability and greater bass extension result, but timbre matching allows complete freedom to mix different models for left and right front, centre and surround if desired.

Freedom and flexibility extend to the four possible mounting options. Use the supplied wall bracket if no tilting of the speaker is needed. If it is, use an Omnimount® type 20.0 or another compatible bracket to get up to 10° of downward tilt. If using a tabletop stand for your screen, simply do the same with the speakers, using the optional table stand. Finally, there is an optional floor stand that supports the speaker at the ideal listening height.

**Description:** 2.5-way vented-box system  
**Frequency Range:** -6dB at 55Hz and 42kHz  
**Frequency Response:** 65Hz – 22kHz ±3dB  
on reference axis  
**Sensitivity:** 88dB spl (2.83V, 1m)  
**Power Handling:** 25W - 100W into 8Ω on  
unclipped programme

**Normal Impedance:** 8 ohms (minimum 3.5 ohms)

**Dispersion:** Description: within 2dB of  
reference response  
Horizontal: over 40° arc  
Vertical: over 10° arc

**Dimensions:** H 794mm W 195mm D 115mm  
H 31.3" W 7.7" D 4.6"  
(including wall plate)

**Weight:** 6.8 kg / 15 lbs.

## B&W Bowers & Wilkins

B&W Group Ltd  
Dale Road  
Worthing West Sussex  
BN11 2BH England

T +44 (0) 1903 221800  
F +44 (0) 1903 221801  
info@bwgroup.com  
www.bwspeakers.com

UK Group (UK Sales)  
T +44 1903 221 500  
E uksales@bwgroup.com

B&W Group North America  
T +1 978 664 2870  
E marketing@bwgroupusa.com

B&W Group Asia Ltd  
T +852 2 869 9916  
E showroom@bwgroup.hk