



Redefining the mini-monitor

For many years, audiophiles have held quality small speakers in high regard for their superb imaging and detail. With its striking design and a host of premium Bowers & Wilkins technologies brought to bear, the PM1 is set to become the mini-monitor of choice.

Technical Specifications

Technical features	Nautilus™ tube loaded tweeter with carbon fibre reinforced aluminium dome Kevlar® fibre cone bass / midrange Flowport™ Matrix™
Description	2-way vented-box system
Drive units	1x 25mm (1in) reinforced aluminium dome high-frequency 1x 130mm (5in) woven Kevlar® cone bass / midrange
Frequency range	-6dB at 42Hz and 60kHz
Frequency response	48Hz - 22kHz ±3dB on reference axis
Dispersion	Within 2dB of reference response Horizontal: over 60° arc Vertical: over 10° arc
Sensitivity	84dB spl (2.83V, 1m)
Harmonic distortion	2nd and 3rd harmonics (90dB, 1m) <1% 110Hz - 22kHz
Nominal impedance	8Ω (minimum 5.1Ω)
Crossover frequency	4kHz
Recommended amplifier power	30W - 100W into 8Ω on unclipped programme
Max. recommended cable impedance	0.1Ω
Dimensions	Height: 331mm (13in) Width: 191mm (7.5in) Depth: 250mm (9.8in) cabinet only 293mm (11.5in) including grilles and terminals
Net weight	9.3kg (20.5lb)
Finishes	Cabinet real wood veneers: Mocha Gloss Grille: Black

FS-PM1

Floor stand

Dimensions	Height: 620.5mm (25.6in) excluding spikes Width: 268mm (10.6in) Depth: 300mm (11.8in)
-------------------	---